

CARE. TRUST. RESPONSIBILITY

## **AUDREY A7-1**

### LARGE & STYLISH 21.5" ALL-IN-ONE POS TERMINAL



As part of the Audrey Family by Partner Tech the Audrey A7-1 with its 21.5 inch display represents the largest All-in-one Terminal ever built by Partner Tech. It stands for Partner Tech's future vision of the POS with stylish features, innovative design with a wide screen display. A technologically rich solution that offers industrial grade performance with a high-quality design that will make a dramatic statement in your store's environment or hospitality area. Completely fanless with various processors to choose, advanced and fast memory and storage options, and 5 years of warranty the Audrey A7-1 is a future proof POS Terminal for many years to come. The terminal supports up to three displays running simultaneously which means that next to the standard second customer display a third monitor for digital signage can be connected via the HDMI port. Furthermore this All-in-one Terminal with its VESA mounting options can be placed on a pole or against a wall to use it as Panel PC. With the optional PS-104 stand you can transform the A7 into a kiosk with the display in portrait mode, an integrated printer and many more peripherals. The combination of performance in a large and stylish design differentiates the Audrey A7-1 from traditional POS solutions offered in the market today.

#### SPECIAL FEATURES

All-in-one POS with 21.5" TFT-LCD
10-point PCAP touch
Up to 7th Generation Intel® Core™ i5 (Kaby Lake) High
performance CPU
Fanless Design
High speed storage with M.2 PCIe Gen3.0 SSD
DDR4 RAM up to 32 GB
Support up to 3 independent displays (Operation, Customer and Digital Signage)
Slim and stylish design for retail and hospitality

#### OPTIONAL

Windows POSReady 7 - only with Intel Bay Trail and Skylake CPU
Linux (Ubuntu)
PS-103 printer stand with Powered USB Hub
Kiosk mode with PS-104 stand
Multi-reader with MSR, IC Card Reader, Fingerprint,
RFID, i-Button
2 x 20 VFD
10.1" Customer Display / optional with touch



# **AUDREY A7-1**

MODELL		AUDREY A7-1			
Display	Max Resolution	1920 x 1080			
	Size	21.5"			
	Brightness	300 nits			
	Contrast	1000:1			
	Response Time	22 ms typ			
	Supported Color	16.7M			
	Viewing Angle	Right 89° Left 89° / Upper 89° Lower 89°			
	Tech- nology	TFT-LCD with LED backlight			
	Touch	10-point PCAP touch			
	CPU (fanless)	POS Ready 7, Windows 10 IoT, Linux (Ubuntu) Intel® Celeron® J1900 (Bay Trail) 2.00 GHz up to 2.40 GHz, Quad Core Intel® Celeron® 3955U (Skylake), 2.00 GHz, Dual Core Intel® Core™ i3-6100U (Skylake), 2.30 GHz, Dual Core Intel® Core™ i5-6300U (Skylake), 2.40 GHz up to 3.00 GHz, Dual Core  Windows 10 IoT (64Bit), Linux (Ubuntu) Intel® Celeron® J3455 (Apollo Lake) 1.50 GHz up to 2.30 GHz, Quad Core Intel® Celeron® 3965U (Kaby Lake), 2.20 GHz, Dual Core Intel® Core™ i3-7100U (Kaby Lake), 2.40 GHz, Dual Core Intel® Core™ i5-7300U (Kaby Lake), 2.60 GHz up to 3.50 GHz, Dual Core			
	Memory	Apollo Lake & Bay Trail: 4GB, 8GB DDR3L			
		Skylake & Kaby Lake: 4GB, 8GB, 16GB DDR4  Apollo Lake & Bay Trail: 128GB / 256GB M.2 SATA SSD			
	Storage	Skylake & Kaby Lake: 128GB / 256GB M.2 PCIe Gen3.0 x2 SSD			
I/O Interface		Apollo Lake, Skylake & Kaby Lake  2 x Serial ports, RS232 (RJ45), 0V/5V/12V selection by BIOS (COM1, COM2)  2 x RJ45, IEEE 802.3 10/100/1000 Mbps Ethernet  4 x USB 3.0  1 x RJ11 Cash Drawer (for 2 cash drawers)  1 x DC 12 V input power-jack  1 x DC 12 V out  1 x Line-out  1 x HDMI  1 x VGA	Bay Trail  3 x COM RS232 (RJ-45), 0V/5V/12V selection by BIOS (COM1, COM2, COM3)  1 x RJ-45 Ethernet  1 x USB 3.0 & 3 x USB 2.0  1 x RJ-11 Cash drawer control (for 2 cash drawers)  1 x DC 12 V input power-jack  1 x DC+12V Out  1 x Audio Line-out  1 x HDMI  1 x VGA		
Expansion Slot	Internal	1 x Mini-PCle			
Speaker	Power	1 x 3 Watts			



### **AUDREY A7-1**

MODELL		AUDREY A7-1			
Optional	Expansion I/O	Bay Trail: A) 1 x COM + 1 LPT B) 1 x 12V + 1 x 24V Powe- red USB	Apollo Lake: A) 2 x COM B) 1 x COM + 1 x LPT C) 1 x 12V + 1 x 24V Powered USB	Skylake & Kaby Lake:  A) 2 x COM Port  B) 1 x COM + 1 x LPT Port  C) 1 x COM + 2 x USB 3.0  D) 2 x USB 3.0 + 1 x 12V + 1  x 24V Powered USB	
Configuration	Attached Peripherals	PS-103 printer stand with Powered USB Hub Kiosk mode with PS-104 stand Multi-reader with MSR and IC Card Reader and (Fingerprint or RFID or i-Button) 10.1" Customer Display CD-101C / optional with touch 2 x 20 VFD Apollo Lake, Skylake and Kaby Lake CPUs support up to 3 independent displays (Operation, Customer and Digital Signage)			
	Management	Intel AMT and Intel V-Pro (Only support for i5 CPU)			
	Colors Black + Silver Grey; Rose Gold + Silver				
Others	VESA Mount. 75 x 75				
	Material	Aluminum stand and back, plastic frame			
	Certifications	CB, EMC (CE, FCC, VCCI, BSMI), BSMI			
Power	Power Adapter AC-In		AC-In 100~240V / DC-Out 12 V, 90 W	In 100~240V / DC-Out 12 V, 90 W	
Dimensions	w/o stand	531(W) x 339 (H) x 45.7 (16.5) (D) mm			
	with stand	531(W) x 390 (H) x 200 (D) mm			
Temperature	Operating	5°C ~ 40°C			
	Storage	-15°C ~ 60°C			
Humidity	Operating	15% ~ 80%			
	Storage	15% ~ 80%			

\*Specifcation is subject of change without prior notice.











+386 1 566 25 20

EUROPE +49 40 450 635-0 UNITED KINGDOM +44 1928 579 707 IBERIA +34 913 120632

ADRIA

info@partner-tech.eu sales-uk@partner-tech.eu comercial@partner-tech.eu prodaja@partner-tech.eu