



IQ Base Transmitter

## IQ Base™ Transmitter

The IQ Base Transmitter is a fast and reliable pager transmitter designed to work with all JTECH pagers. With UHF technology, your signal has a unique system ID which eliminates interference.

The IQ Base can manage up to 9999 pagers and supports all JTECH guest and staff pagers including: QuietCall®, SmartCall® IQ, StaffCall® IQ and GuestCall® IQ pagers.

### Additional Features

The IQ Base Transmitter is beautifully designed with an 8-line LED backlit interface and quick setup.

#### UHF Technology

Up to 2-mile range with unique ID to prevent signal interference.

#### Durable

Built with high-quality materials for maximum durability and industry leading performance.

#### Bright LED Display

Easy-to-read LED backlit digital display. Quick buttons make repeated communications a breeze.

#### Smart Alerts

Out-of-Range and Search ensures guest contact and minimizes pager loss.

#### Manager, Staff & Guest Pagers

Supports the full line of JTECH pagers.

#### Manager Button

Instantly call the manager to provide additional assistance as necessary.

Call today for more information

800.321.6221  
www.jtech.com



# IQ Base™

## Guest & Staff Paging Transmitter

### Specifications

<b>Display</b>	<ul style="list-style-type: none"> <li>&gt; 2 x 3 inch 8 line display</li> <li>&gt; Blue LED backlit digital screen</li> <li>&gt; Water-resistant polyurethane</li> </ul>
<b>Interfaces</b>	<ul style="list-style-type: none"> <li>&gt; Serial: DB9- DCE (female) Connector</li> <li>&gt; Data Rates: 1200, 9600, 38400, 57600</li> <li>&gt; Characters: 8 Data Bits</li> <li>&gt; Stop Bits: 1</li> </ul>
<b>Electrical</b>	<ul style="list-style-type: none"> <li>&gt; Frequency range: 450 - 468 MHZ</li> <li>&gt; FCC Identifier: WDC-IQBASE-N</li> <li>&gt; IC Identifier: 7752A-IQBASE-N</li> <li>&gt; Channel Spacing: 12.5 KHz</li> <li>&gt; Speed / Baud Rate: 512/1200 bps</li> </ul>
<b>Power</b>	<ul style="list-style-type: none"> <li>&gt; DC 12V, 3.5A, SMPS</li> <li>&gt; RF Output (Watts): 2 Watts</li> <li>&gt; Format: POCSAG</li> </ul>
<b>Extended Range Technology</b>	<ul style="list-style-type: none"> <li>&gt; UHF Frequency</li> <li>&gt; Unique System ID eliminates interference</li> <li>&gt; Up to 2-mile range</li> </ul>

### Dimensions

<b>IQ Base Transmitter</b>	Length: 9.37 inches (23.7 cm)	Width: 5.5 inches (14 cm)
	Height: 1.75 inches (4.3 cm)	Weight: 1.6 lbs (0.72 k)

### Works With:



GuestCall® Pagers



QuietCall® & SmartCall



StaffCall IQ® Pagers



Call today for more information  
**800.321.6221**

#### JTECH

1400 Northbrook Parkway  
Suite 320  
Suwanee, GA 30024, USA  
www.jtech.com  
Tel: (800) 321.6221



#### About JTECH, an HME Company

JTECH is the largest onsite paging company in the world and the leading provider of onsite messaging solutions for hospitality, healthcare, retail, church nurseries and other markets. Headquartered in Suwanee, Georgia, JTECH is a wholly-owned subsidiary of HME, Inc., an innovative technology company focused on enhancing productivity and customer service for multiple markets including restaurant and pro audio since 1971.

©2018 JTECH, an HME Company logo and product names are registered trademarks of HM Electronics, Inc. All rights reserved.

PS18-TXIQ-v2