

CARE. TRUST. RESPONSIBILITY

TOUCH TERMINAL SP-635-BZ

ECONOMICAL AND EFFICIENT



The economical but powerful POS Touch Terminal has now become bezelfree with projected capacitive touch to meet the standard of today's requirements. Our new SP-635-BZ is the right system in view of cost efficiency and performance. The now bezelfree SP-635-BZ is equipped with Intel® Celeron™ J1900 Quad Core processor. It is fanless to guarantee reliability and low maintenance. The monitor is flexible and can be adjusted to meet the requirements of any workplace – whether with convenient VESA / wall mount or wide tilt angle.

There are different possibilities to connect a customer display (2x20 VFD) or a second monitor e.g. for digital signage purposes. To round up the SP-635-BZ Touch POS Terminal has a wide range of helpful peripheral options.

SPECIAL FEATURES

Powerful Intel® Celeron™ J1900 quad core processor Supports up to 8GB RAM

Supports up to 8GB RAM

Flexible modular design and dual display support Spill and dust resistant front panel, IP 65

Convenient VESA / wall mount and wide tilt angle monitor $% \left(1\right) =\left(1\right) \left(1\right) \left($

Green low power consumption

OPTIONAL

Customer display (2x20 VFD or 7")
2nd VGA port for monitor support
3-track MSR, IC card reader, RFID reader,
Fingerprint sensor, i-Button / Dallas / Addimat, LPT port



SP-635-BZ

Item	SP-635-BZ
CPU	Intel® Celeron™ J1900 (2.00GHz up to 2.42GHz), quad core, 2MB L2 Cache, fanless
LCD	15" TFT-LCD, resolution 1024 x 768, brightness 350 nits, Contrast 700:1, LED backlight
Touch	Projected Capacitive Multi Touch
RAM	2 x DDR3L SO-DIMM, supports up to 8GB
Storage	1 x 2.5" SATA HDD or SSD (option)
LAN	1 x RJ-45 10/100/1000 BASE-T Gigabit Ethernet
I/O Interface	3 x COM (DC+0/5/12V: COM 1-2 BIOS selection, COM 3 by jumper) 3 x USB 2.0 1 x USB 3.0 1 x RJ-45 Ethernet 1 x VGA 1 x Mini PCIe (internal) 1 x LPT port (factory option with MOQ)
Speaker	1 x 1W speaker (internal)
Operating System	Windows 7, POSReady 7, Windows 8.1, Windows 10, Linux (ubuntu)
Power Supply	AC100~240V/DC+12V, 5.4A, 65W power adaptor
Dimensions	360mm (W) x 240mm (D) x 365mm (H)
Environment	Operating: Storage: Temperature: 0°C ~ +40°C -20°C ~ +60°C Humidity: 15% ~ 80% 15% ~ 80%
Options	3-track MSR, customer display (2x20 VFD, CD-703A), 2nd monitor, IC card reader, LF/HF NFC/RFID reader, fingerprint sensor, i-Button/Dallas/Addimat SSD, LPT port (factory option with MOQ)
Color	black

*Specifcation is subject of change without prior notice. 11/19







EUROPE +49 40 450 635-0 UNITED KINGDOM +44 1928 579 707 IBERIA +34 913 120632 ADRIA +386 1 566 25 20

+49 40 450 635-0 info@partner-tech.eu +44 1928 579 707 sales-uk@partner-tech.eu +34 913 120632 comercial@partner-tech.eu +386 1 566 25 20 prodaja@partner-tech.eu